

# Are you paying too much for Pressure transducers?



## Transducers



**STANDARD FEATURES**

- Interchangeable with Competitor's models
- Fluid filled system (or new pushrod design)
- 6pin Bayonet Connector
- 6"Stem with/without 18"Flex Hose
- 0.5% combined error
- 80% Output Calibration
- 750oF (400oC) Rating
- Ranges from 0-500 to 0-20,000psi
- Standard Diaphragm INCONEL


## Transmitters



**STANDARD FEATURES**

- Interchangeable with Competitor's models
- Fluid filled system (or new pushrod design)
- 6pin Bayonet Connector
- 6"Stem with/without 18"Flex Hose
- 0.5% combined error
- 80% Output Calibration
- 750oF (400oC) Rating
- Ranges from 0-500 to 0-20,000psi
- Standard Diaphragm INCONEL

## Extruder Rupture Discs



Inconel End Disc  
 750oF (400oC) Rating  
 5% Accuracy  
 Stock Ranges :  
 1500, 2500, 3500, 5500, 6500,  
 7500, 8500, 9500, 10500psi  
 Maximum 20,000psi  
 Standard Thread (1/2-20UNF)

**OPTIONS**  
 Custom Threads, Tip Designs

## Accessories



CABLES - Transducer / Transmitter

CONNECTORS - 6Pin, 8Pin

CLEANING / CUTTING KIT

### Digital Melt Pressure Gauge



Large 5-DIGIT Display (0.8")  
LED Bar Graphs (Process & Set Value)  
90-260VAC Power  
6" Stem + 30" Flex Hose (MG200, MGJ)  
1% combined error  
750oF (400oC) Rating  
Ranges from 0-500 to 0-20,000psi  
Rotateable Display (270deg)  
Standard Thread (1/2-20UNF)  
Temp Sensors J (MGJ)  
Retransmission : 4-20mA, 0-5,10VDC

#### OPTIONS

12, 24VDC Power  
Mercury Free  
12" Stem  
60" Flex Hose (MG200, MGJ)  
Temp Sensors K, Pt100  
Optional Hastelloy, Triple Wear Tip  
Diamond Particulate  
Retransmission : 0-5,10VDC

### Melt Pressure Indicators / Alarms



**Call Bill for more information  
or a quote!  
(816) 468-7577**

**THERMAL TECH EQUIPMENT** Co., Inc

2704 NE 78<sup>th</sup> Street, Kansas City, MO 64119